

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Amana Tool 45° Lock Miter Carbide-Tipped 2-Flute

Thank you for shopping with us! The lock miter is an interlocking edge-to-edge joint, typically used at the corners of casework. Used in a table-mounted router, run at reduced speed, this bit cuts both halves of the joint. The same setup of bit and fence cuts both parts. One part is laid flat on the tabletop and fed across the cutter. The second is braced vertically against the fence and fed across the cutter. For best results, use in a table-mounted router. Full color instruction manual included. #55390 **Warning:** Maximum RPM = 18,000

Item #	Manufacturer	Diameter	Diameter (D1)	Cut Height, Length, or Width	Flute	Overall Length	Shank	Angle	Price
55393	Amana Tool	1 1/2 in	12.1mm	1/2 in	2	1 5/8 in	1/4 in	45 deg	\$87.04
55391	Amana Tool	1 5/8 in	13.2mm	5/8 in	2	1 3/4 in	1/4 in	45 deg	\$72.38
55389	Amana Tool	1 3/4 in	6.4mm	7/8 in	2	2 1/8 in	1/2 in	45 deg	\$98.81
55390	Amana Tool	2 11/16 in	9.2mm	1-3/16 in	4	2 5/8 in	1/2 in	45 deg	\$95.29