Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



Amana Tool Double-Face Melamine, Korton & Veneers

Thank you for shopping with us! Can't find what you need? Give us a call and we'll be happy to assist you. Alterations to the geometry and plate thickness provide improved results in certain melamine boards. The bevel angle of the ATB grind is far more acute (35°), and the plate is thinner than our standard melamine blades. Note: P.H. denotes pin-hole configuration, if applicable. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle. Warning: Before use, read saw blade safety guidelines in Amana's catalog.

2° Negative Hook • 35° 'High-ATB' Grind



Item #	Manufacturer	Diameter	Bore	Grind	Kerf	Pinholes	Plate	Teeth	Bevel	Hook Angle	Price
MSB1080	Amana Tool	10 in (250 mm)	5/8 in	H-ATB	0.118 in		0.087 in	80	35 deg bevel angle	2 deg negative hook angle	\$128.77
MSB1080C	Amana Tool	10 in (250 mm)	5/8 in	H-ATB	0.118 in		0.087 in	80	35 deg bevel angle	2 deg negative hook angle	\$134.56
MSB1080-30	Amana Tool	10 in (250 mm)	30 mm	H-ATB	0.118 in	2/7/42 & 2/10/60	0.087 in	80	35 deg bevel angle	2 deg negative hook angle	\$128.77
MSB1296	Amana Tool	12 in (300 mm)	1 in	H-ATB	0.118 in		0.087 in	96	35 deg bevel angle	2 deg negative hook angle	\$150.90

MSB1296-30 Amana Tool 12 in (300 mm) 30 mm H-ATB 0.118 in $\frac{2}{7}$ 0.18 in $\frac{2}{7}$ 0.087 in 96 35 deg bevel 2 deg negative angle hook angle \$150.90