

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Everlast Plex-Cut Saws - TC45

Thank you for shopping with us!

Special tooth design for cutting plastics where melting is a problem, such as nylon, acrylic, plexiglass, lucite, ABS, lexan, and PVC pipe. Good for material thickness up to 3/8". Please call for cutting materials in excess of 3/8". Special design available for vinyl extrusion cutting.

Modified Triple Chip Grind - TC45 - This design starts with TCG configuration, but the STR (raker) tooth has small 45 degree chamfer. The addition of this chamfer, along with special clearances, provides the best possible finish on double face laminate and solid surface materials. This design provides good service life with excellent surface finish on table saws and radial arm saws.



Item #	Manufacturer	Bore	Diameter	Grind	Kerf	Note	Plate	Teeth	Hook Angle	Price
PC860	Everlast	5/8 in	8 in	TC45	0.106 / 2.7 mm	--	0.072 in / 1.8 mm	60	5 deg	\$131.70
PC1080	Everlast	5/8 in	10 in	TC45	0.106 / 2.7 mm	--	0.072 in / 1.8 mm	80	5 deg	\$197.62
PC1280	Everlast	1 in	12 in	TC45	0.125 / 3.0 mm	--	0.087 in / 2.2 mm	80	5 deg	\$217.78
PC121058V	Everlast	5/8 in	12 in	TC45	0.128 / 3.3 mm	Designed for cutting vinyl extrusions	0.098 in / 2.5 mm	100	-5 deg	\$257.84
PC1410	Everlast	1 in	14 in	TC45	0.150 / 3.7 mm	--	0.110 in / 2.8 mm	100	5 deg	\$246.08

PC141058V	Everlast	5/8 in	14 in	TC45	0.150 / 3.7 mm	Designed for cutting vinyl extrusions	0.118 in / 3.0 mm	100	-2 deg	\$268.89
PC1410V	Everlast	1 in	14 in	TC45	0.146 / 3.7 mm	Designed for cutting vinyl extrusions	0.110 in / 2.8 mm	100	5 deg	\$262.71
PLJ141005AF	Everlast	1 in	14 in	AR/AFB	0.130 / 3.3 mm	5 degree alternate face bevel	0.102 in / 2.6 mm	100	20 deg	\$298.68
PLN16457	Everlast	1 in	16 in	AR 4+1	0.148 / 3.8 mm	--	0.110 in / 2.8 mm	45	20 deg	\$270.58
PC1660	Everlast	1 in	16 in	TC45	0.148 / 3.8 mm	--	0.110 in / 2.8 mm	60	10 deg	\$286.66
PLJ161004	Everlast	1 in	16 in	TC45	0.134 / 3.4 mm	--	0.102 in / 2.6 mm	100	20 deg	\$313.97
PLJ161005AF	Everlast	1 in	16 in	AR/AFB	0.125 / 3.2 mm	5 degree alternate face bevel	0.102 in / 2.6 mm	100	20 deg	\$389.86
PC1860	Everlast	1 in	18 in	TC45	0.175 / 4.4 mm	--	0.134 in / 3.4 mm	60	10 deg	\$302.90
PC1810	Everlast	1 in	18 in	TC45	0.175 / 4.4 mm	--	0.134 in / 3.4 mm	100	10 deg	\$379.72
PLJ181004	Everlast	1 in	18 in	TC45	0.142 / 3.6 mm	--	0.102 in / 2.6 mm	100	20 deg	\$404.98
PLJ181204	Everlast	1 in	18 in	TC45	0.142 / 3.6 mm	--	0.102 in / 2.6 mm	120	20 deg	\$415.53
PLJ201004	Everlast	1 in	20 in	TC45	0.142 / 3.6 mm	--	0.102 in / 2.6 mm	100	20 deg	\$448.50
PLJ201204	Everlast	1 in	20 in	TC45	0.142 / 3.6 mm	--	0.102 in / 2.6 mm	120	20 deg	\$500.55
PC960	Everlast	5/8 in	9 in	TC45	0.115 / 2.9 mm	--	0.087 in / 2.2 mm	60	-5 deg	\$135.63
PC1080V	Everlast	5/8 in	10 in	TC45	0.106 / 2.7 mm	--	0.072 in / 1.8 mm	80	5 deg	\$197.62
PC1240	Everlast	1 in	12 in	TC45	0.134 / 3.4 mm	--	0.095 in / 2.4 mm	40	15 deg	\$195.76
PC1480N	Everlast	1 in	14 in	TC45	0.150 / 3.7 mm	--	0.110 in / 2.8 mm	80	-2 deg	\$234.31
PC1680	Everlast	1 in	16 in	TC45	0.148 / 3.8 mm	--	0.110 in / 2.8 mm	80	10 deg	\$325.63
PC1610	Everlast	1 in	16 in	TC45	0.148 / 3.8 mm	--	0.118 in / 2.8 mm	100	5 deg	\$398.19

PC1620	Everlast	1 in	16 in	TC45	0.160 / 4.1 mm	--	0.118 in / 2.8 mm	120	5 deg	\$418.20
PC1880	Everlast	1 in	18 in	TC45	0.175 / 4.4 mm	--	0.134 in / 3.4 mm	80	10 deg	\$381.64
PLJ181205AF	Everlast	1 in	18 in	TC45	0.142 / 3.6 mm	5 degree alternate face bevel	0.102 in / 2.6 mm	120	20 deg	\$485.41