
Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



Freud Thin Kerf Rip Blades: Series LU87R

Thank you for shopping with us!

Application: Heavy-Duty Ripping Blades for Underpowered Saws This blade gives new life to underpowered table saws and radial arm saws because the thin kerf does not require much horsepower. The Perma-SHIELD® coating helps this blade pull 1/3 less on the saw, which translates to over 33% more cutting power. The ideal working range is from 3/4" to 2 3/4" thick. Premium TiCo™ HI-Density Carbide Ripping Blend for Maximum Performance. Thin Kerf allows for faster feed rate and reduced waste. Positive Hook Angles for fast cutting and easy feeding in ripping applications. Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch build-up. Ideal For: Heavy-Duty Ripping Blades For Underpowered Saws. Depth of cut (3/4" to 2-3/4"). *TIP:* Maintain a proper feed rate. Feeding too slow causes burning of the material. Feeding too fast can be dangerous and produces a poor dull cut.

Item #	Kerf	Diameter	Arbor	Bevel	Plate	Teeth	Туре	Manufacturer	Price
LU87R006M20	0.087 in	160 mm	20 mm	10 deg	.063 in	14 ATB	Perma-SHIELD - Ideal for Track Saws	Freud Tools	\$40.05
LU87R008	0.087 in	8 in	5/8 in	15 deg	.063 in	22 ATB	Perma-SHIELD	Freud Tools	\$52.26
LU87R009	0.094 in	9 in	5/8 in	15 deg	.071 in	22 ATB	Perma-SHIELD	Freud Tools	\$56.07
LU87R010	0.094 in	10 in	5/8 in	15 deg	.071 in	24 FLAT	Perma-SHIELD	Freud Tools	\$56.83
LU87R012	0.099 in	12 in	5/8 in	15 deg	.071 in	30 ATB	Perma-SHIELD	Freud Tools	\$56.83