## Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: info@eoasaw.com Website: www.eoasaw.com



## **Tenryu Steel-Pro® Series**

Thank you for shopping with us! Low RPM Dry Cut Saws. Circular Saws. Tenryu's steel cutting carbide-tipped saw blade gives industrial performance. Cut ferrous metals (mild steel) faster, cleaner, and easier. Save time, money, the environment, and your respiratory health. Tenryu's complete series of steel cutting saw blades called "Steel-Pro®" makes light work out of all kinds of mild steel: steel studs, steel sheet, steel pipe, channel, threaded rod, and many more. Specially formulated C-6 carbide grade, combined with our unique tip design, resists breakage on impact and lasts much longer than standard carbides or abrasive discs. Special tooth geometry with "inserted" tooth design greatly improves security of the tip, efficiency, and durability. Abrasive discs throw sparks and lots of dust, including unhealthful fiberglass. Steel-Pro® blades reduce spark production and eliminate abrasive wheel dust. Abrasive discs wear guickly, requiring frequent blade changes. Steel-Pro® blades allow you to keep working, eliminating down time for frequent blade changes. In addition, Steel-Pro® cuts 5 to 10 times faster than abrasives. Typically, one Steel-Pro® blade will outlast somewhere between 15 to 30 abrasive blades. Think of all that non-productive "down time." Abrasive discs leave a sharp blurr at the cutting edge that must be removed later. Steel-Pro® blades cut clean, eliminating this extremely time-consuming aftercut process. "Time is money"—Steel-Pro® saves you both! Each Blade Features: -Rugged plates and specially-formulated carbide tips with a special tooth grind for fast, clean cuts. -High guality cuts without the clouds of dust and scorch marks associated with friction blades. -Cool cuts that leave the workpiece edge free of burrs. -With fewer blade changes, reduced cost-per-cut and maximized performance for the operator. Note: Please note all safety instructions before use and adhere to instructions for maximum RPM speeds. Always wear eye protection that meets ANSI Z87.1 requirements and properly functioning upper and lower blade guards. For cordless saws, see also Cord-Free for mild steel saw blades

| Item #       | Manufacturer | Application  | Arbor     | Kerf  | Diameter | Grind | Teeth | Price   |
|--------------|--------------|--|-----------|-------|----------|-------|-------|---------|
| PRF-18538BW  | Tenryu       | Good for 1/8 in to 1/4 in wall thickness   | 5/8 in KO | 0.079 | 7 1/4 in | ATB   | 38    | \$48.60 |
| PRF-18548BW  | Tenryu       | Signature Steel-Pro blade for mechanical construction; up to 1/8 in wall thickness | 5/8 in KO | 0.079 | 7 1/4 in | ATB   | 48    | \$50.40 |
| PRF-18556CB  | Tenryu       | More teeth for cutting thin sheet steel (flat stock only))                         | 5/8 in KO | 0.071 | 7 1/4 in | ATAF  | 56    | \$62.10 |
| PRF-18570CBN | Tenryu       | For very thin sheet steel (flat stock only)  | 5/8 in KO | 0.069 | 7 1/4 in | ATB   | 70    | \$65.70 |

| PRF-21048BWTenryuGeneral purpose; up to 1/8 in wall thickness; for 2 in saw5/8 in KO0.0878 1/4 inMTCG48\$67.50PRF-23048CBNTenryuGeneral purpose; up to 1/8 in wall thickness; for 9 in saw1 in0.0879 inATB48\$72.00PRF-25550DTenryuGeneral purpose; up to 1/8 in wall thickness; for 10 in dry<br>cutters only1 in, 5/8 in0.09110 inTCG50\$109.80PRF-30560DTenryuGeneral purpose; up to 3/8 in wall thickness; for 12 in dry<br>cutters (Jepson, Makita, etc)1 in0.09812 inTCG60\$115.20PRF-35572DTenryuGeneral purpose; up to 3/8 in wall thickness; for 14 in dry<br>cutters (Jepson, Makita, etc)1 in0.09414 inTCG72\$171.00PRF-35572DTenryuFor dry cutters; or foam insulated panel cutting w/Makita<br>beam saw1 in0.102TCG80\$468.00PRF-185548CBWTenryuFor mechanical construction; up to 1/8 in wall thickness5/8 in KO0.0797 1/4 inATB48\$50.49 | PRF-20348CBN  | Tenryu   | General purpose; up to 1/8 in wall thickness; for Milwaukee<br>saw | 5/8 in KO    | 0.087 | 8 in     | MTCG | 48 | \$67.68  |
|---|---------------|----------|--|--------------|-------|----------|------|----|----------|
| PRF-25550DTenryuGeneral purpose; up to 1/8 in wall thickness; for 10 in dry<br>cutters only1 in, 5/8 in0.09110 inTCG50\$109.80PRF-30560DTenryuGeneral purpose; up to 3/8 in wall thickness; for 12 in dry<br>cutters (Jepson, Makita, etc)1 in0.09812 inTCG60\$115.20PRF-35572DTenryuGeneral purpose; up to 3/8 in wall thickness; for 14 in dry<br>cutters1 in0.09414 inTCG72\$171.00PRF-40580DTenryuFor dry cutters; or foam insulated panel cutting w/Makita<br>   | PRF-21048BW   | Tenryu   |  | 5/8 in KO    | 0.087 | 8 1/4 in | MTCG | 48 | \$67.50  |
| PRF-25550DTenryuGeneral purpose; up to 3/8 in wall thickness; for 12 in dry<br>cutters (Jepson, Makita, etc)1 in0.09110 inTCG50\$109.80PRF-30560DTenryuGeneral purpose; up to 3/8 in wall thickness; for 12 in dry<br>cutters (Jepson, Makita, etc)1 in0.09812 inTCG60\$115.20PRF-35572DTenryuGeneral purpose; up to 3/8 in wall thickness; for 14 in dry<br>cutters1 in0.09414 inTCG72\$171.00PRF-40580DTenryuFor dry cutters; or foam insulated panel cutting w/Makita<br>beam saw1 in0.102TCG80\$468.00  | PRF-23048CBN  | Tenryu   | General purpose; up to 1/8 in wall thickness; for 9 in saws        | 1 in         | 0.087 | 9 in     | ATB  | 48 | \$72.00  |
| PRF-30500DTenryuGeneral purpose; up to 3/8 in wall thickness; for 14 in dry<br>cutters1 in0.098 12 inTCG60\$113.20PRF-35572DTenryuGeneral purpose; up to 3/8 in wall thickness; for 14 in dry<br>cutters1 in0.094 14 inTCG72\$171.00PRF-40580DTenryuFor dry cutters; or foam insulated panel cutting w/Makita<br>beam saw1 in0.102TCG80\$468.00   | PRF-25550D    | Tenryu   |  | 1 in, 5/8 in | 0.091 | 10 in    | TCG  | 50 | \$109.80 |
| PRF-35572DTenryucutterscuttersIn0.09414 inTCG72\$171.00PRF-40580DTenryuFor dry cutters; or foam insulated panel cutting w/Makita<br>beam saw1 in0.102TCG80\$468.00  | PRF-30560D    | Tenryu   |  | 1 in         | 0.098 | 12 in    | TCG  | 60 | \$115.20 |
| beam saw I In 0.102 ICG 80 <b>\$468.00</b>  | PRF-35572D    | Tenryu   |  | 1 in         | 0.094 | 14 in    | TCG  | 72 | \$171.00 |
| PRF-18548CBWD TenryuFor mechanical construction; up to 1/8 in wall thickness5/8 in KO0.0797 1/4 inATB48\$50.49  | PRF-40580D    | Tenryu   |  | 1 in         | 0.102 |          | TCG  | 80 | \$468.00 |
|   | PRF-18548CBWD | ) Tenryu | For mechanical construction; up to 1/8 in wall thickness           | 5/8 in KO    | 0.079 | 7 1/4 in | ATB  | 48 | \$50.49  |