Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #0756102, Model 75006PR Electro-Hydraulic Hole Puncher \$6,050.00

Thank you for shopping with us! Now with Power Retract! Our heaviest duty model, the 75006PR develops 26.9 tons of pressure and will produce up to 15/16" diameter round holes. In approximately 4 seconds, the 75006PR can punch through material up to 1/2" thick. Like all Hougen-Ogura Punches, its single body design makes it easy to use anywhere. Easily confirm the hole position with the jog down feature. Punch automatically returns to the starting position after the punching cycle is complete. If punch ever resists returning to the home position, squeeze the trigger for power feed return. The unit has eye bolts on both sides for easy attachment of a lift assist or a counter-balancer for improved ergonomics. Work stand, foot switch, 13/16 in punch & die, and tool kit are standard.

75006PR SPECIFICATIONS Part No. 0756102 - 120V				
Pressure (Tons)	26.9			
Approx. Punching Speed	4 secs			
Max Hole Size - Round	15/16" - (23.8mm)			
Max Hole Thickness - Round	1/2 " - (12.7mm)			
Max Hole Size - Oblong	11/16" x 13/16" (18mm x 21mm)			
Max Hole Thickness - Oblong	1/2" - (12.7mm)			
Max Throat Depth	1-31/32" - (50mm)			
120V 50-60Hz AC	13 Amps / 1460 Watts			
Weight (less work stand)	62.9 lbs - (28.5 kg)			
Shipping Weight	82.6 lbs - (37.5 kg)			
Dimensions	ons 20.59" L x 6.3" W x 18.23" D			

Hougen-Ogura Punches are designed for mild & structural steel, but can be used in other materials. Using in stainless or other materials significantly reduces the capacity.

SPF		

Manufacturer Hougen

Includes Work stand, foot switch, 13/16 in punch & die, and tool kit are standard