

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



306005 Carbide Tipped Brad
Point Boring Bit L/H 5mm Dia x



206005 Carbide Tipped Brad
Point Boring Bit R/H 5mm Dia

Item #206005, Amana Tool High Performance Ditec™ Brad Point Boring Bits Carbide-Tipped 70MM Long \$25.92

Thank you for shopping with us!

Ditec™ dowel drills feature special grinding and high performance carbide for ultra long lasting applications.

Industrial Brad Point Boring Bits are coated with a non-stick coating for longer lasting cutting edge and tool life. Amana Tool® dowel drills are coated with a special Polytetrafluoroethylene (PTFE), a non-stick color coating. In cases where the carbide tip cutting edges are coated, there is no need to sand the coating off before use. Once the tool starts drilling, the coating is cleared off the needed cutting edge right away. Amana's coating is applied onto the bit at a temperature of 570° F. The coating reduces the friction between the chip and the body inside the flute and it helps to clear the chips out of the hole during the drilling to create a cooler drilling area, no burning, and longer lasting cutting edge.

SPECIFICATIONS	
Manufacturer	Amana Tool
Cut Height, Length, or Width	40 mm
Note	Not to be used in portable drills or handheld routers.
Overall Length	70 mm
Shank	10 mm