Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



Item #3135XP, Vortex Series 3100XP Two Flute 1/2 x 1 " Xtreme Performance" Compression Spiral \$112.57

Thank you for shopping with us!

" XP," which stands for Xtreme Performance, is specifically manufactured to provide maximum tool life in melamine, high pressure laminated particle board, and MDF materials. Users can expect 3-5 times more tool life as compared to standard compression spiral geometry. The compression geometry will provide a chip-free edge on both sides of the material.



Upcut Spirals

- The upcut spiral is a right hand spiral with a right hand rotation of cut. An upcut spiral will cause the chips to be "augered" upwards during cutting. This can be particularly useful in slotting cuts or where chip removal is a problem. Upcut spiral bits have a tendency to "lift" the part in some cases. Additional holding power or stepped cutting may be required.
- Upcut spiral bits will leave a smooth cut on the bottom of a thru cut and tend to leave some fuzzing on the top edge in certain materials.
- ▼ Upcut spirals straight plunge/drill and have good end cutting geometry.



Downcut Spirals

- A downcut spiral (right hand cut, left hand spiral) causes the chip flow to be directed downward. It also helps hold down the part being cut. The edge quality on the part is smooth on the top and tends to be fuzzy on the bottom in certain materials.
- ▼ The downward chip flow can sometimes cause clogging problems particularly in a blind slotting situation. Downcut bits tend to preload the routing system and can substantially improve part hold down in a marginal routing setup.
- Downcut tools CAN NOT be used to plunge straight into wood and should be ramped into the part.



Compression Spirals

- A compression spiral is designed with both upcut and downcut flutes. The upcut and downcut flutes compress the material being cut preventing chipping or fuzzing on the top and bottom of the cut.
- Compression spirals are used extensively for cutting double sided laminates, and can be used on natural woods where edge fuzzing is a problem.

SPECIFICATIONS	
Manufacturer	Vortex Tool
Diameter	1/2 in
Cut Height, Length, or Width	1 in
Flute Geometry	Compression
Flute	2
Overall Length	3 in
Rotation	Right
Shank	1/2 in
Upcut Length	0.25 in