

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)

---



### **Item #41632, Techniks PowerCOAT 50mm ER32 Dust Seal Nut - Torque 100 ft/lbs \$82.00**

Thank you for shopping with us!

Use with our dust seal that snaps into the nut to seal and protect your collets and cutting tools. Match the ER collet size and shank size to the dust seal specifications. -40% more holding power than bearing nuts. -Balanced to 25,000 RPM. -Better rigidity and T.I.R. (runout). PowerCOAT Nuts outperform bearing nuts! -Rubber bearing seals on bearing nuts eventually fail, and then dust contaminates bearings to make them freeze up. -Uncoated threads limit holding power. -Bearing nuts cannot be balanced because they have moving parts so cutting tools wear prematurely. CNC Routers run better with PowerCOAT! PowerCOAT nuts greatly reduce friction between the nut, collet shoulder, and tool holder threads to increase down-force on the collet, collapsing tighter around the tool shank. This improves holding power and runout (T.I.R.). Better T.I.R. means cutting is faster and smoother, and tool life is also improved.

SPECIFICATIONS	
Manufacturer	Techniks
Diameter	50mm
Recommended Torque	100 ft/lbs
Style	ER32 HS Dust Seal Nut
Thread Size/Length	M40x1.5
Wrench	0.4616
Height	27.5mm