Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



Item #45798, Amana Tool 3/4" D x 1/2" CH x 1/4" Shank CNC Double-Edge Folding V & Rectangular Groove for Shaping Aluminum Composite Material Carbide-Tipped Router Bit \$84.40

Thank you for shopping with us!

These bits are widely used as cladding for many diverse applications such as office buildings, hospitals, convention centers, airports, hotels. Routing V-shaped & Rectangular grooves, whereby the aluminum cover and a part of the polyethylene core is removed, allows folding/creasing the remaining material by hand.

Designed for cutting and scoring aluminum sandwich materials including:

- Aluminum, Clay, Zinc & Wood Composite Panels
- Aluminum Composite Materials (ACM)
- Aluminum Composite Panel (ACP)*
- Aluminum 5052
- ALPOLIC® Copper Composite Material (CCM)
- Alucobond®
- Alupanel®
- Dibond®
- Durabond**
- e-panel[™]
- Etalbond®
- · Phenolics
- Plastic/Acrylic
- Plexiglas®
- Titanium Composite Material (TCM)
- Wood

*Aluminum Composite Panel (ACP) is a type of ACM flat panel that consists of two thin aluminum sheets bonded to a non-aluminum core. ACPs are frequently used for external cladding or facades of buildings, insulation, and signage. **Durabond is a polyethylene core with 0.3mm colored aluminum sheet on either side, prefinished requiring no decoration.

SPECIFICATIONS	
Diameter	23/32 in
Cut Height, Length, or Width	1/2 in

SPECIFICATIONS	
Diameter (D1)	0.080 in
Length	
Manufacturer	Amana Tool
Note	
Overall Length	2 1/4 in
Shank	1/4 in
Туре	V
Angle	135 deg / 22.5 (a1)