


## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #46193-K, Amana Tool CNC Solid Carbide Spektra™ Extreme Tool Life Coated Compression Spiral 1/2 Dia x 1-3/8 x 1/2 Inch Shank **\$124.50**

Thank you for shopping with us! Special unique carbide for longer lifetime in abrasive material. Designed for CNC applications requiring high feed rates and a clean finish. Particularly suitable for double-sided melamine or laminated material. Flawless compression cuts. Our Spektra™ bits feature a nAco® nanocomposite coating with an extreme nanohardness and heat resistance. With a brilliant distinctively-tinted coloring, nAco® provides additional improvements in four critical aspects of router tooling: -nAco® coating is a micro-thin ceramic coating that enables the tool's cutting edge to retain crucial sharpness and lubricity. This provides longevity and produces cutting results of the highest quality. -Coating prevents high heat and oxidation, which is detrimental to cutting tool performance. - Multi-colored hues, while attractive, will dissipate upon use and yet coating will remain fully effective. -nAco® offers approximately 4,500 Vickers for impressive solid hardness on cutting areas of the tool, for an increase up to 2.5 times compared to uncoated bits. Note: Blue based color dissipates immediately upon use. nAco® nanocomposite coating will not wear off. Excellent for cutting: CFRP, Double-Sided Melamine, Laminate, Melamine Particle Board, MDF, Oriented Strand Board (OSB)\*, Veneered Plywood, Wood \*Oriented Strand Board is an engineered wood particle board.



## SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Diameter</b>	1/2 in
<b>Cut Height, Length, or Width</b>	1 3/8 in
<b>B1</b>	12mm
<b>Flute</b>	2
<b>Overall Length</b>	3 1/2 in
<b>Shank</b>	1/2 in

SPECIFICATIONS

Pack Quantity

1