Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #46290-5, Amana Tool 5-Pack CNC 2D/3D Carving Flat Bottom 0.10 Deg Angle x 1/16 Dia x 5/16 x 1/4 Shank x 2 Inch Long x 3 Flute Solid Carbide ZrN Coated Router Bit \$166.16

Thank you for shopping with us.

Specially designed for 2D and 3D CNC profiling and carving in plastic, aluminum, and wood with machines such as " i-Carver," CNC Shark®, ShopBot®, Datron & Carvewright $^{\text{TM}}$. The high-shear ball nose tips cut smooth 2D and 3D contours with reduced stepping, while the proprietary ZrN coating (applied by the physical vapor deposition coating process) provides high resistance to wear, sharper cutting edges, extended tool life, and less friction & heat buildup.

Applications:

- Precision 2D and 3D large scale carving
- Dimensional signage
- 3D millwork
- 2D and 3D contouring, profiling, modeling, and pattern-making for cabinetry, sign-making, furniture-making, and jewelry mold-making
- \bullet Compatible with CarveWright $^{\mathtt{m}}$ and CompuCarve woodworking systems
- Perfect for model-makers on large 3D milling profiles in abrasive EPS foam and other materials

Benefits of Zirconium Nitride (ZrN) Coating

- Creates a harder and tougher cutting edge, allows for a prolonged cutting edge life, and helps to prevent the build-up of material in the flutes while cutting
- Has the tendency to run/spin much faster than an uncoated tool
- Optimized flute geometry and low Total Indicated Runout (TIR) guarantees clean cuts, essentially eliminates sanding and reduces chatter (where the machine or work-piece vibrates) under high chip loads (when used with low TIR spindles)
- High flute volume supports high feed rates and chip loads
- High aspect ratio for single pass deep-reach cutting
- Flute geometry optimized for cutting sign foam, sign board, hardwoods, thermoplastics, and phenolic composites

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	1/16 in

SPECIFICATIONS	
Cut Height, Length, or Width	5/16 in
Flute	3
Overall Length	2 in
Radius	
Shank	1/4 in
Туре	Flat Bottom, ZrN
Angle	0.10 deg
No. of Pieces	5