

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #46332, Amana Tool Solid Carbide Slow Spiral Flute Plunge Upcut 1/2" x 1" x 1/2" Shank Router Bit **\$77.21**

Thank you for shopping with us!

Specially designed to provide an excellent finish in hardwoods, solid surface, and hard plastics. Choose Upcut if an excellent finish on the bottom of the surface is required, and choose Downcut for an excellent finish on the top of the surface.

Specially designed to provide an excellent finish in:

- Acrylonitrile Butadiene Styrene (ABS)
- Fomex®
- Hard Plastics
- Hardwood
- High Impact Polystyrene (HIPS)
- Hydroxy-Terminated Polyether (HTPE)
- Low Density Polyethylene (LDPE)
- LubX®
- Perspex® Cast Acrylic Sheet
- Poly (methyl methacrylate) (PMMA)
- Polyethylene Terephthalate Glycol-Modified (PETG / PET-G)
- Polyoxymethylene (POM); also known as Acetal, Polyacetal, and Polyformaldehyde
- Sign Foam
- Solid Surface
- StarBoard® (King StarBoard 'R') High Density Polyethylene Sheet (HDPE)
- Teflon®
- Thermoplastic Polyolefin (TPO) -Urethane

Recommended RPM: 20,000-21,000.

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	1/2 in
Cut Height, Length, or Width	1 in
Flute Geometry	Upcut
Flute	4
Overall Length	3 in
RPM	20,000-21,000
Shank	1/2 in