

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)

---



**Item #46334, Amana Tool Solid Carbide Slow Spiral Flute Plunge Upcut 1/2" x 1 1/2" x 1/2" Shank Router Bit**  
**\$119.63**

Thank you for shopping with us!

Specially designed to provide an excellent finish in hardwoods, solid surface, and hard plastics. Choose Upcut if an excellent finish on the bottom of the surface is required, and choose Downcut for an excellent finish on the top of the surface.

**Specially designed to provide an excellent finish in:**

- Acrylonitrile Butadiene Styrene (ABS)
  - Fomex®
  - Hard Plastics
  - Hardwood
  - High Impact Polystyrene (HIPS)
  - Hydroxy-Terminated Polyether (HTPE)
  - Low Density Polyethylene (LDPE)
  - LubX®
  - Perspex® Cast Acrylic Sheet
  - Poly (methyl methacrylate) (PMMA)
  - Polyethylene Terephthalate Glycol-Modified (PETG / PET-G)
  - Polyoxymethylene (POM); also known as Acetal, Polyacetal, and Polyformaldehyde
  - Sign Foam
  - Solid Surface
  - StarBoard® (King StarBoard 'R') High Density Polyethylene Sheet (HDPE)
  - Teflon®
  - Thermoplastic Polyolefin (TPO) -Urethane
- Recommended RPM: 20,000-21,000.**

### SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Diameter</b>	1/2 in
<b>Cut Height, Length, or Width</b>	1 1/2 in

## SPECIFICATIONS

**Flute Geometry**

Upcut

**Flute**

4

**Overall Length**

3 1/2 in

**RPM**

20,000-21,000

**Shank**

1/2 in