

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #46354-K, Amana Tool CNC Solid Carbide Spektra™ Extreme Tool Life Coated Mortise Compression Spiral 1/2" Dia x 1 1/4" x 1/2" Shank 2-Flute

\$154.32

Thank you for shopping with us!

These tools have a much shorter upcut section than the standard compression tools. They are ideal for mortising, grooving, and dado.

Excellent for cutting: MDF/HDF, Laminate, Melamine, Plywood, Wood. Recommended RPM 20,000-21,000.

Our Spektra™ bits feature a nACo® nanocomposite coating with an extreme nanohardness and heat resistance. With a brilliant distinctively-tinted coloring, nACo® provides additional improvements in four critical aspects of router tooling:



- nACo® coating is a micro-thin ceramic coating that enables the tool's cutting edge to retain crucial sharpness and lubricity. This provides longevity and produces cutting results of the highest quality.

- Coating prevents high heat and oxidation, which is detrimental to cutting tool performance.

- Multi-colored hues, while attractive, will dissipate upon use and yet coating will remain fully effective.

- nACo® offers approximately 4,500 Vickers for impressive solid hardness on cutting areas of the tool, for an increase up to 2.5 times compared to uncoated bits.

Note: Blue based color dissipates immediately upon use. nACo® nanocomposite coating will not wear off.



SPEKTRA™
EXTREME TOOL LIFE COATING



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	1/2 in
Flute	2
Cut Height, Length, or Width	1 1/4 in
Overall Length	3 in
Pack Quantity	1
Shank	1/2 in
RPM	Max RPM 20,000 - 21,000