

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #46410, Amana Tool CNC Spiral Flute Plunge Solid Carbide 5/32" x 5/8" x 1/4" Shank Router Bit - 2-Flute, Downcut \$42.03

Thank you for shopping with us!

Spiral-flute bits combine a shearing action in cutting with an augering action in chip clearance. The shearing action yields an especially clean, accurate cut, while the augering action clears chips from the cut.

The 'Upcut' shears from the bottom up, pulling chips from the bottom up, thus allowing deeper penetration with less stress on the tool. An excellent choice for mortising. The 'Downcut' cuts from the surface down leaving a smooth edge at the surface.

Special unique carbide grade, increased clearance geometry, and razor-sharp cutting edges with polished flutes, provide a superior finish and longer tool life, especially in abrasive materials. Great for production settings and excellent for creating grooves and dado cuts in softwood, hardwood, plywood, and composite materials. Primarily used on CNC machines and other automatic routers. Can be used with handheld and table-mounted portable routers.



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	5/32 in
Cut Height, Length, or Width	5/8 in
Flute Geometry	Downcut
Flute	2

SPECIFICATIONS

Note	--
Overall Length	2 1/2 in
Shank	1/4 in