Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com





Item #46424-K, Amana Tool Solid Carbide Spektra™ Extreme Tool Life Coated Upcut Spiral Ballnose 3/32 Radius x 3/16 Dia x 1/2 x 1/4 Shank x 2-1/2 Inch Long x 2 Flute Router Bit \$59.73

Thank you for shopping with us! Amana Tool's high mirror-finish solid carbide upcut spiral ballnose router bits are designed to eliminate tool marks that commonly appear when used with plastic and solid surface materials. Due to the highly polished finish and unique tool geometry, the spiral ballnose router bit delivers superior surface finish of at least 28 Ra (roughness average) in various materials. The upcut router bits also eject chips up, to help prevent chip out on the bottom of the material. Constructed of special grade solid carbide, Amana Tool spiral ballnose router bits last longer than traditional router bits and deliver superior cutting performance with plastics. The bits are ideal for use in a variety of applications spanning the mechanical, medical, and woodworking industries. Our Spektra™ bits feature a nACo® nanocomposite coating with an extreme nanohardness and heat resistance. With a brilliant distinctively-tinted coloring nACo provides additional improvements in four critical aspects of router tooling. nACo coating is a micro-thin ceramic coating which enables the tool's cutting edge to retain crucial sharpness and lubricity. This provides longevity and produces cutting results of the highest quality. Coating prevents high heat and oxidation which is detrimental to cutting tool performance. Multi-colored hues, while attractive, will dissipate upon use and yet coating will remain fully effective. nACo offers approximately 4,500 Vickers for impressive solid hardness on cutting areas of the tool, for an increase up to 2.5 times compared to uncoated bits. Note: Blue based color dissipates immediately upon use. nACo® nanocomposite coating will not wear off. Excellent for Cutting: Plastic Acrylic Acrylic Stone Acrylonitrile Butadiene Styrene (ABS) Corian Coroplast®* Fomex® High Impact Polystyrene (HIPS) High Pressure Laminates (HPL) Hydroxy-Terminated Polyether (HTPE) Low Density Polyethylene (LDPE) LubX® Perspex® Cast Acrylic Sheet Plexiglas® Poly (methyl methacrylate) (PMMA) Polyethylene Terephthalate Glycol-Modified (PETG / PET-G) Polyoxymethylene (POM), also known as Acetal, Polyacetal and Polyformaldehyde. Sign Foam Solid Surface StarBoard® (King StarBoard 'R') High Density Polyethylene Sheet (HDPE) Thermoplastic Polyolefin (TPO) Urethane Wood *A soft plastic cardboard made with super soft super flexible PVC. Note: Blue based color dissipates immediately upon use. nACo® nanocomposite coating will not wear off.

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	3/16 in
Cut Height, Length, or Width	1/2 in
Flute Geometry	Upcut
Flute	2
Overall Length	2 1/2 in
Radius	3/32 in
Shank	1/4 in