## Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



## Item #46432, Amana Tool Solid Carbide Slow Spiral Flute Plunge Downcut 1/2" x 1" x 1/2" Shank Router Bit \$77.21

Thank you for shopping with us!

Specially designed to provide an excellent finish in hardwoods, solid surface, and hard plastics. Choose Upcut if an excellent finish on the bottom of the surface is required, and choose Downcut for an excellent finish on the top of the surface.

## Specially designed to provide an excellent finish in:

- -Acrylonitrile Butadiene Styrene (ABS)
- -Fomex®
- -Hard Plastics
- -Hardwood
- -High Impact Polystyrene (HIPS)
- -Hydroxy-Terminated Polyether (HTPE)
- -Low Density Polyethylene (LDPE)
- -LubX®
- -Perspex® Cast Acrylic Sheet
- -Poly (methyl methacrylate) (PMMA)
- -Polyethylene Terephthalate Glycol-Modified (PETG / PET-G)
- -Polyoxymethylene (POM); also known as Acetal, Polyacetal, and Polyformaldehyde
- -Sign Foam
- -Solid Surface
- -StarBoard<sup>®</sup> (King StarBoard 'R') High Density Polyethylene Sheet (HDPE) -Teflon<sup>®</sup>

-Thermoplastic Polyolefin (TPO) -Urethane **Recommended RPM:** 20,000-21,000.

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	1/2 in
Cut Height, Length, or Width	1 in
Flute Geometry	Downcut
Flute	3

SPECIFICATIONS	
Overall Length	3 in
RPM	20,000-21,000
Shank	1/2 in