Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #46562, Amana Tool Solid Carbide CNC Foam Cutting Downcut Square End Spiral 1/8" D x 1-1/16" CH x 1/8" Shank Router Bit \$53.79

Thank you for shopping with us! Ensure your foam projects are milled with unparalleled accuracy detail and clarity. Achieve both precision and depth for foam carving and milling applications. Provides deeper cuts and larger slices with fewer passes in thick materials, resulting in improved productivity and less assembly. The upcut spiral ejects chips away from the workpiece. **Specifically designed for milling:**

- Polyurethane Foam
- Expanded Polystyrene (EPS)
- Polyethylene Foam
- Extruded Polystyrene Foam (XPS)
- Crosslinked Polyethylene Foam (XLPE)
- Ethafoam**
- Ethylene-vinyl Acetate Foam (EVA)
- Expanded Polypropylene (EPP)*
- Flexible Polyurethane Foam (FPF)
- Fomex®
- High Density Urethane (HUD Board)
- PALFOAM™
- Polycarbonate (Lexan[™])†
- Polylam**

*Expanded polypropylene (EPP) is a foam form of polypropylene. **Ethafoam Polyethylene and Polylam are durable flexible closed-cell foams with excellent memory. †Recommendation: Use the slowest suggested feed rates and the shortest bits necessary for cutting and routing Lexan™.





For thick

material with upcut chip removal. For 2D & 3D CNC routing applications. Router collet reducer RB-102 (1/4 to 1/8) available for 1/8 shank bits.

SPECIFICATIONS

Manufacturer Amana Tool

SPECIFICATIONS	
Diameter	1/8 in
Cut Height, Length, or Width	1 1/16 in
Flute Geometry	Downcut
Flute	2
Overall Length	3 in
Shank	1/8 in
Туре	Flat Bottom/Square End