

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Item #508400, Amana Tool Carbide-Tipped Adjustable ACM Scoring Set 8 Inch Dia x 2x20T, 18 Deg, 5/8 Bore (Industrial)

\$197.10

Edge of Arlington offers free shipping in the United States when you choose flat rate shipping.

Carbide-Tipped - V-Groove with 2.0 (0.080") - 3.0mm (0.118") V-Flat Bottom.



Designed for scoring Aluminum

Composite (sandwich) Materials with 60°, 90°, 108°, and 135° angle V-grooves with flat bottom. Set contains two saw blades and a shim set. Add the shims between the blades to achieve your desired flat bottom cut width. Widely used for cladding many diverse exterior and interior applications. The long lasting durability of the material makes it an excellent choice for buildings, signage, displays, etc.

Excellent for scoring: Aluminum, Clay, Zinc & Wood Composite Panels; Aluminum Composite Materials (ACM); Aluminum Composite Panel (ACP)*; ALPOLIC® Copper Composite Material (CCM); Alucobond®; Alupanel®; Dibond®; Durabond**; e-panel™; Etalbond®; Titanium Composite Material (TCM); Trespa®.

The materials are used on facades and interior wall surfaces that can be found in office buildings, hospitals, convention centers, airports, and hotels, along with exterior signage.


*ACP is a type of ACM flat panel that consists of two thin aluminum sheets bonded to a non-aluminum core. ACPs are frequently used for external cladding or facades of buildings, insulation, and signage.

**Durabond is a polyethylene core with 0.3mm colored aluminum sheet on either side, pre-finished requiring no decoration.

Warning: This set requires a custom zero clearance throat plate.

Warning: Not to be used with portable saws.

Warning: Before use, read saw blade safety guidelines in [Amana's catalog](#).



SPECIFICATIONS

B1	0.161 in
Bore	5/8 in
Grind	ACM
Kerf	Range: 10.2-11.2mm
Manufacturer	Amana Tool
Note	Warning: This set requires a custom zero clearance throat plate. Warning: Not to be used with portable saws. Shim set #DSS-108 & instruction booklet included.
Specs-Misc	2.0-3.0mm/0.078-0.118" Flat Bottom Range
Teeth	2x20
Angle	45 °