

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #51737-K, Amana Tools Solid Carbide Spektra™ Extreme Tool Life Coated Spiral Finisher 1/2 Dia x 1-1/8 x 1/2 Shank Downcut Router Bit \$114.00

Thank you for shopping with us! Those seeking improved surface finishes in either plastics or hardwoods do well to move up to Amana Tool's 3 flute Low Helix Finishers. The unbeatable combination of three keen edges and a gentle 10° helix, equates to a stiffer tool that minimizes both part movement and edge burring, leaving a smooth finish. Leaves an extra-high surface finish. Excellent for Cutting: Plastic Acrylic Stone Acrylonitrile Butadiene Styrene (ABS) Corian Composite Plastic Coroplast®* Delrin® Foam Fomex® Hardwood High Impact Polystyrene (HIPS) High Pressure Laminates (HPL) Hydroxy-Terminated Polyether (HTPE) Low Density Polyethylene (LDPE) LubX® Perspex® Cast Acrylic Sheet Poly (methyl methacrylate) (PMMA) Polyethylene Terephthalate Glycol-Modified (PETG / PET-G) Polyoxymethylene (POM), also known as Acetal, Polyacetal and Polyformaldehyde. Precision Board Sign Foam Softwood Solid Surface StarBoard® (King StarBoard 'R') High Density Polyethylene Sheet (HDPE) Thermoplastic Polyolefin (TPO) Urethane *A soft plastic cardboard made with super soft super flexible PVC. Our Spektra™ bits feature a nACo® nanocomposite coating with an extreme nanohardness and heat resistance. With a brilliant distinctively-tinted coloring nACo provides additional improvements in four critical aspects of router tooling. nACo coating is a micro-thin ceramic coating which enables the tool's cutting edge to retain crucial sharpness and lubricity. This provides longevity and produces cutting results of the highest quality. Coating prevents high heat and oxidation which is detrimental to cutting tool performance. Multi-colored hues, while attractive, will dissipate upon use and yet coating will remain fully effective. nACo offers approximately 4,500 Vickers for impressive solid hardness on cutting areas of the tool, for an increase up to 2.5 times compared to uncoated bits. Note: Blue based color dissipates immediately upon use. nACo® nanocomposite coating will not wear off.

SPECIFICATIONS

| | |
|-------------------------------------|------------|
| Manufacturer | Amana Tool |
| Diameter | 1/2 in |
| Cut Height, Length, or Width | 1 1/8 in |
| Overall Length | 3 1/2 in |

| SPECIFICATIONS | |
|----------------|---------|
| Flute Geometry | Downcut |
| Flute | 3 |
| Shank | 1/2 in |