

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #55294, Amana Tool Carbide-Tipped 82 Degree Countersink with Adjustable Low Friction Depth Stop, 3/8 Dia x 1/8 Drill Dia x 1/4 Inch Quick Release Hex Shank

\$32.70

Edge of Arlington offers free shipping in the United States when you choose flat rate shipping.

Quick release 1/4" Hex Shank, 2-wing with HSS M2 slow spiral [fully ground drill DIN 1897](#).

Low friction polymer collar. No surface scratches or burn marks!

These tools combine carbide countersink, high speed steel drill bit, and free-spinning low friction depth-stop. The countersink leaves a clean hole edge and the adjustable depth-stop doesn't mar the surface. The large openings around the collar allow the chips to clear effectively and eliminate clogging.

Excellent for Drilling: Natural Woods, Man-Made Boards, MDF, Chipboard, Plywood, Aluminum/Non-Ferrous, Aluminum Composite Material (ACM), Composites, Composite Decking Materials.

Replacement NF1/4 x 1/4 set screw #67070 for tightening depth stop.

Replacement NF1/4-28 x 3/16 set screw #67083 for drill tightening.

Replacement 1/8 x 5/32 double-sided hex key #5019 (included).

Warning: When drilling aluminum/non-ferrous materials, for optimal results and extended tool life use lubricant or air cooling. Make sure the material is fixed and drill is stable during drilling.

SPECIFICATIONS

Cut Height, Length, or Width

9 mm

Diameter (D1)

1/8 in

Manufacturer

Amana Tool

Overall Length

2 3/8 in

Screw Size

6

Shank

1/4 in

Angle

49 °