

Edge of Arlington Saw & Tool, Inc.


124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #55437, Amana Tool Carbide-Tipped Adjustable Flat Panel Bead Instile™ & Rail System 1-5/8" Dia x 3/16" Radius x 1/2" Shank Set

\$181.46

Thank you for shopping with us! Amana Tool Carbide-Tipped Adjustable Flat Panel Bead Instile™ & Rail System 1-5/8" Dia x 3/16" Radius x 1/2" Shank Set Instile™ System: Cut precise grooves to provide undersized plywood veneered panels with a snug, rattle-free fit. Adjust the panel groove width (3/16" to 9/32" for 1/4" plywood; 7/16" to 17/32" for 1/2" plywood). Cuts frame stock from 5/8" through 1 1/4" thick. Designed to cut precise grooves to provide undersized plywood veneered panels with a snug rattle-free fit. Each set includes 2 pieces (1 for stile cuts and 1 for rail cuts and shims). Bits in these flat panel stile and rail sets have profile and groove or rabbet cutters and ball bearing guide mounted on a 1/2" shank. Respacing of the components should only be necessary—using the provided shims—after the cutters have been resharpener. Guide straight cuts with the fence; use the pilot bearing only for cuts on



curved rails or stiles.  " Thick" Configuration Assembly (7/16 to 17/32" for 1/2" plywood panel - 1 1/4" doors) " Thin" Configuration Assembly (3/16" to 9/32" for 1/4" plywood panel - 3/4" doors) Includes full color instruction manual. Instructional video below:

SPECIFICATIONS

Manufacturer

Amana Tool

SPECIFICATIONS

Diameter	1 5/8 in
Cut Height, Length, or Width	6 in
Bearing(s)	
Note	Includes full color instruction manual.
Overall Length	3 11/32 in
Radius	3/16 in
Shank	1/2 in
Type	Bead
Angle	N/A
Material Thickness	1/4 in plywood - 3/16 to 9/32 in; 1/2 in plywood - 7/16 to 17/32 in