

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com


Website: www.eoasaw.com



Item #55438, Amana Tool Carbide-Tipped Adjustable Flat Panel Mission (Straight)™ & Rail System 1-5/8" Dia x 1/2" Shank Set

\$209.36

Thank you for shopping with us! Amana Tool Carbide-Tipped Adjustable Flat Panel Mission (Straight)™ & Rail System 1-5/8" Dia x 1/2" Shank Set Instile™ System: Cut precise grooves to provide undersized plywood veneered panels with a snug, rattle-free fit. Adjust the panel groove width (3/16" to 9/32" for 1/4" plywood; 7/16" to 17/32" for 1/2" plywood). Cuts frame stock from 5/8" through 1 1/4" thick. Designed to cut precise grooves to provide undersized plywood veneered panels with a snug rattle-free fit. Each set includes 2 pieces (1 for stile cuts and 1 for rail cuts and shims). Bits in these flat panel stile and rail sets have profile and groove or rabbet cutters and ball bearing guide mounted on a 1/2" shank. Respacing of the components should only be necessary—using the provided shims—after the cutters have been resharpened. Guide straight cuts with the fence; use the pilot bearing only for



cuts on curved rails or stiles.

Thick" Configuration Assembly (7/16 to 17/32" for 1/2" plywood panel - 1 1/4" doors) " Thin" Configuration Assembly (3/16" to 9/32" for 1/4" plywood panel - 3/4" doors) Includes full color instruction manual. Instructional video below:



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	1 5/8 in
Cut Height, Length, or Width	6 in
Bearing(s)	
Note	Includes full color instruction manual.
Overall Length	3 11/32 in
Radius	N/A
Shank	1/2 in
Type	Mission (Straight)
Angle	N/A
Material Thickness	1/4 in plywood - 3/16 to 9/32 in; 1/2 in plywood - 7/16 to 17/32 in