


Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #77-509, Freud 1/2 in Dia, 1 1/4 in CH, 2 Flute, 1/2 in Shank Premier Solid Carbide Mortise Compression Spiral Bit \$82.86

Thank you for shopping with us!



Application: Mortises or grooves with a perfect top surface, or through-cuts in thin double-sided veneers and laminates

-Shorter up shear length allows bit to be used for grooves and mortises without chipping top surface.

-Also ideal for through-cuts in double-sided sheets that are 5/8" thick or less.

-Combination of up and down shear flutes eliminates chipping on both sides of double-sided panels.

-Routs melamine, veneer plywood, and other double-sided materials, as well as hardwood and softwood.

-Use on CNC and other automatic routers as well as handheld and table-mounted portable routers.

-Double flute spirals are for extra clean cuts at faster feed rates.

-Black I.C.E.™ coating for cool cutting edge and superior chip evacuation. Black I.C.E.™ + Freud TiCo™ Hi-Density Carbide = 2X increased life and performance vs. standard uncoated bits. Black ICE Router Bits—the slickest technology in solid carbide router bits—protects solid carbide cutting edge by creating a slick, lubricant-like action for a cool cutting edge and superior chip evacuation.



SPECIFICATIONS

Manufacturer

Freud Tools

SPECIFICATIONS

Diameter	1/2 in
Cut Height, Length, or Width	1 1/4 in
Flute	2
Overall Length	3 1/2 in
Shank	1/2 in
Upcut Length	1/4 in