

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



CUTS



Item #D0632GPX, Diablo 6-1/2" x 32 Tooth Wood & Metal Carbide Saw Blade

\$30.80

Thank you for shopping with us!

Diablo's new 6-1/2" Wood & Metal saw blade is the industry's first multi-purpose saw blade for cutting clean wood and wood with nails, up to 2" material thickness, as well as metal ranging from 3/32"-1/4" wall thickness and 1/4"-1" diameter. The versatility of these new blades provides the ability to use the same blade to cut wood and metal so now users can focus on completing the job more efficiently rather than wasting time with changing tools and saw blades.

The Diablo-made TiCo carbide tips, which are specially designed for this blade, coupled with the blade's Chamber-Alternate Tooth Design (C-ATB) provides impact resistance for cutting wood with nails as well as the durability for creating clean, burr-free cuts in metal. Optimized for corded and cordless saws, this new blade cuts 2X lumber, wood with nails, angle iron, channel, flat bar, steel studs, and threaded rod.

Specially formulated Diablo-made TiCo Carbide withstands impact, reduces wear, and lasts longer in wood and metal cutting applications. Chamfer-Alternate Top Bevel (C-ATB) tooth design cleanly shears through wood while providing the durability needed for clean, burr-free cuts in metal. Tri-Metal Shock Resistant Brazing allows carbide tips to withstand extreme impact for maximum durability in wood and metal applications. Perma-SHIELD® non-stick aluminum coating protects the blade against heat, gumming, and corrosion.

Advanced Laser-Cut Stabilizer Vents traps noise and vibration for maximum stability, keeping the blade cool with accurate cuts in wood and metal. Laser-Cut Thin Kerf Design provides less resistance and heat buildup for ease of cut, accuracy, and long cutting life in wood and metal. Laser-Cut Arbor reduces vibration and premature wear for accurate blade rotation on corded and cordless saws.

Cuts up to 2" material thickness in clean wood & wood with nail cutting applications. Cuts 3/32"-1/4" wall thickness in steel studs, channel, angle iron, pipe, tubing, plate, and bar stock. Cuts 1/4" - 1" diameter threaded rod.

Ideal For: Wood with nails as well as the durability for creating clean, burr-free cuts in metal.

SPECIFICATIONS

Manufacturer	Diablo Tools
Arbor	5/8 in
Diameter	6 1/2 in
Teeth	32 C-ATB
Hook Angle	5 deg
Kerf	.059 in
Plate	.051 in
Application	Wood with nails as well as the durability for creating clean, burr-free cuts in metal
Unit Price	--
Pack Quantity	1