Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #DT120T24, Amana Tool Carbide-Tipped Ditec™ 2000 Conical/Adjustable Type Scoring 120mm Dia x 24T ATB, 8 Deg, 20mm Bore, Scoring Set


Thank you for shopping with us!

Used on panel saws with separate scoring units for chip-free cuts on both sides of the material. With conical type scoring blades, the kerf width changes with depth of penetration. Used in combination with our industrial saw blades '7' series only (#714721), etc). Also used in combination with the Ditec $^{\text{TM}}$ series panel saw main blades. Kerf range should match the main blade.

- √ Exclusive DITEC[™] Carbide Tips
- √ Higher Reliability & Lower Maintenance
- √ Low Noise Level
- √ Laser Cut Saw Bodies
- √ Excellent Cutting Quality

Instructions for grinding: For maintenance grinding, use fine grit (D400 to D600) diamond wheels. To match the factory grind, use a slower than normal feed rate. Damaged teeth can be replaced by any grade of carbide tooth. Replacing of a large number of teeth will, of course, shorten the life of the saw blade. Since the carbide in the DITEC™ is harder than other carbides, it is critical that you protect them from "thermal shock" if an adjacent tooth is replaced. Heat absorbed during the brazing process will seriously degrade the DITEC™ carbide.

Warning: Before use, read saw blade safety guidelines in <u>Amana's</u> <u>catalog.</u>



SPECIFICATIONS	
Diameter	120 mm
Bore	20mm
Grind	Conical

SPECIFICATIONS	
Kerf	4.4mm to 5.4mm
Machine	Altendorf , Martin, SCMI
Plate	2.8 mm
Teeth	24
Manufacturer	Amana Tool