

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #HG10483-30, Amana Tool Carbide Tipped Hollow Ground 10 Inch Dia x 48T HG, 10 Deg, 30mm Bore \$198.42

Thank you for shopping with us!

The specially designed saw blade makes exceptionally smooth cuts in melamine and other coated boards, without the need for scoring. The unique hollow grind, which pairs a triple-chip tooth with a raker tooth that's ground to a concave profile, produces crisp clean cuts. The positive hook angle is particularly suitable for use on horizontal sliding table saws, such as those made by Striebig®, Altendorf®, SCM, and Holz-Her®.

Note: P.H. denotes pin-hole configuration, if applicable. Example: 2/10/60 = 2 @ 10mm dia on 60mm circle.

Warning: Before use, read saw blade safety guidelines in [Amana's catalog](#).



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	10 in (253 mm)
Bore	30 mm
Grind	Hollow Grind (HG)
Kerf	0.126 in

SPECIFICATIONS

Pinholes	2/7/42 & 2/10/60
Plate	.087 in
Teeth	48
Hook Angle	10 deg positive hook