## Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com






## Item #HG12600-30, Amana Tool Carbide-Tipped Hollow Ground 12" Dia x 60T HG, -6 Deg, 30mm Bore \$182.66

Thank you for shopping with us!

The specially designed saw blade makes exceptionally smooth cuts in melamine and other coated boards, without the need for scoring. The unique hollow grind, which pairs a triple-chip tooth with a raker tooth that's ground to a concave profile, produces crisp clean cuts. The grind is commonly used in vertical panel saws, such as those made by Striebig® and Holz-Her®. The negative hook angle is particularly suitable for vertical panel saws.

Note: P.H. denotes pin-hole configuration, if applicable. Example:  $2/10/60 = 2 \odot 10$ mm dia on 60mm circle.

Warning: Before use, read saw blade safety guidelines in **Amana's catalog.** 



Melamine Single & Double Sided

SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	12 in (303 mm)
Bore	30 mm
Grind	Hollow Ground (HG)
Kerf	0.126 in
Machine	Holz-Her

SPECIFICATIONS	
Pinholes	2/7/42 & 2/10/60
Plate	0.087 in
Teeth	60
Hook Angle	6 deg negative hook