

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #LM74R010, Freud Glue Line Ripping Blades: Series LM74R \$92.25

Thank you for shopping with us!

Application: Heavy Duty Glue Line Ripping Blades for Superior Finish

This blade's specially designed triple chip tooth design produces extremely smooth, true surfaces for gluing and finish work. There is no need for sanding or jointing after the cut. The ideal working range is from 1/8" to 1" thick. This blade also features laser-cut anti-vibration slots, practically eliminating the vibration that resonates in standard blades. With this ultimate ripping blade, there is no need for stabilizers.

Premium TiCo™ HI-Density Carbide Ripping Blend for Maximum Performance. Heavy-Duty Thick Kerf and Plate ensure a stable, flat blade for long cutting life. Laser-Cut Anti-Vibration Slots drastically reduce vibration and sideways movement in the cut, extending blade life and giving a crisp, splinter-free flawless finish.

Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup. Silver Ice Coating resists corrosion and pitch buildup.

Ideal For: Heavy Duty Glue Line Ripping Blades For Superior Finish. Depth of cut (1/8" to 1").

Tip: For best results, set your saw so that one half of a carbide tip protrudes beyond the material to be cut.

SPECIFICATIONS

Manufacturer	Freud Tools
Diameter	10 in
Arbor	5/8 in
Kerf	0.118 in
Plate	.098 in
Teeth	30
Type	Perma-SHIELD

SPECIFICATIONS

Grind

TCG