

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #LU87R006M20, Freud 160mm Dia, 20mm Arbor, 14 ATB Thin Kerf Rip Blade : Series LU87R

**\$40.05**

Thank you for shopping with us!

#### **Application: Heavy-Duty Ripping Blades for Underpowered Saws**

This blade gives new life to underpowered table saws and radial arm saws because the thin kerf does not require much horsepower. The Perma-SHIELD® coating helps this blade pull 1/3 less on the saw, which translates to over 33% more cutting power. The ideal working range is from 3/4" to 2 3/4" thick. Premium TiCo™ HI-Density Carbide Ripping Blend for Maximum Performance. Thin Kerf allows for faster feed rate and reduced waste. Positive Hook Angles for fast cutting and easy feeding in ripping applications. Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch build-up. Ideal For: Heavy-Duty Ripping Blades For Underpowered Saws. Depth of cut (3/4" to 2-3/4" ). **TIP:** Maintain a proper feed rate. Feeding too slow causes burning of the material. Feeding too fast can be dangerous and produces a poor dull cut.

## SPECIFICATIONS

<b>Kerf</b>	0.087 in
<b>Diameter</b>	160 mm
<b>Arbor</b>	20 mm
<b>Bevel</b>	10 deg
<b>Plate</b>	.063 in
<b>Teeth</b>	14 ATB
<b>Type</b>	Perma-SHIELD - Ideal for Track Saws
<b>Manufacturer</b>	Freud Tools