Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com







Thank you for shopping with us!

Application: Crosscutting Blades for Fine Finish with Underpowered Saws

This Perma-SHIELD® coated blade gives new life to underpowered saws and produces smooth crosscuts in hardwoods, softwoods, and moldings. Coated blades pull 1/3 less on the saw, which translates into 33% more cutting power. Thin kerf blades remove less material than standard carbide blades, thus requiring less horsepower to produce equally good results.

Premium TiCo™ HI-Density Carbide Crosscutting Blend for Maximum Performance. Positive Hook Angle produces a smoother cut and allow for a faster feed rate. Thin Kerf reduces waste and feeds easier. Perma-Shield™ Non-Stick Coating reduces blade drag, protects the blade from corrosion and pitch buildup.

Ideal For: Crosscutting Blades For Fine Finish With Underpowered Saws. Depth of cut (1/2" min to 2-3/4" max).

Tip: If you experience burning on one side of the cut, you should check and adjust the saw's alignment. Consult your saw owner's manual for alignment instructions.

SPECIFICATIONS	
Diameter	12 in
Arbor	1 in
Kerf	.094 in
Plate	.071 in
Teeth	80 ATB
Туре	Perma-SHIELD
Manufacturer	Freud Tools