

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



















Item #MD12-721-30, Amana A.G.E. Series General Purpose Saw Blades: TCG Grind \$101.35


Thank you for shopping with us!

Designed for clean cuts in plywood and single-sided laminates.

These blades are specifically designed for clean cuts in plywood and single-sided laminates. The greater number of teeth, triple-chip grind, and 12° hook angle provide an excellent balance between feed resistance and finish. For a chip-free edge on both top and bottom sides of the double-sided laminates, it is recommended to use a [scoring blade](#) along with these blades.

Warning: Not recommended for cutting non-ferrous alloys and melamine.



	NOT RECOMMENDED	FAIR	GOOD	EXCELLENT
 CHIPBOARD				
 MDF				
 LAMINATE				
 CROSSCUT				
 PLYWOOD				
 RIPPING				
 NON-FERROUS ALLOYS				
 MELAMINE				



Soft / Hardwood Crosscut



Plastic Laminate, Single & Double Sided



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	300 mm
Bore	30 mm
Hook Angle	10 deg
Kerf	0.126 in
Note	--
Pinholes	30mm bore accepts: 2/10/60, 2/7/42, 2/9/46
Plate	0.087 in
RPM	6,200
Teeth	72