Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651


Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com




Item #MD8-608, Amana A.G.E. Series Solid Surface Saw Blades: M-TCG Grind

Thank you for shopping with us!

Excellent for cutting solid surface materials. Specifically designed for cutting solid surface materials such as Avonite®, Dupont Corian®, Wilsonart®, Gibralter®, Earthstone®, Fountainhead®, Surrell®, Staron®, plastic laminate, Plexiglas®, and other acrylic based materials. The modified triple chip grind is especially configured to leave a swirl-free cut in solid surface materials. Thicker than normal steel plates reduce vibration that degrades the cut and shortens tool life. Suitable for a variety of saw configurations. The hook angle virtually eliminates self-feeding when used on a radial arm saws.







SOLID SURFACE



SPECIFICATIONS	
Diameter	8 in
Bore	5/8 in
Grind	M-TCG
Hook Angle	0 deg
Kerf	0.126 in
Pinholes	

SPECIFICATIONS	
Plate	0.087 in
Teeth	60
RPM	9,500
Fits	
Manufacturer	Amana Tool