

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Item #RC-1107, Amana Tool CNC Insert V-Groove 130° x 2 1/8 Dia x 1/2" Shank (Industrial) **\$193.91**

Thank you for shopping with us!

The innovative CNC tool design uses a high grade solid carbide insert knife, which allows for two uses out of each insert. Once the knife shows signs of wear you can rotate the insert for a brand new cutting edge. These industrial 'V' Groove insert router bits were especially designed for applications including:

- Miter folds - "create the perfect joint"
- Signmaking and lettering

Advantages of Insert Tooling

- Long lasting insert knives provide superior smooth quality cuts every time
 - Quick and precise replacement of dull knives
 - Due to insert accuracy, tool life is extended
 - Insert tooling allows for harder grades of carbide
 - Special carbide grades for special applications
 - Knives can be sharpened multiple times without affecting the original profile
 - Cost effective solution compared to replacing brazed router bits
- Secure locking screw system ensures maximum safety and maintains cutting accuracy. CNC router requires quality hold downs to ensure the least possibility of material shifting during operation.

Excellent for cutting—engraving first list item only:

- Aluminum, Brass, Bronze, Copper, Gold, Silver & Carbon Fiber—Engraving Only
- Foam
- Laminate
- Melamine
- MDF/HDF
- Sign Board
- Solid Surface
- Veneered Plywood
- Wood
- Xanita® Board*
- 20lbs High Density Urethane

*When working with Xanita LightBoard panel (X-board®, X-board® plus) we recommend using MDF knives for better results.

SPECIFICATIONS

Diameter

2 1/8 in

SPECIFICATIONS

B1	1 5/32 in
Cut Height, Length, or Width	1/2 in
Edge(s)	1
Knives	Included Gen Purp RCK-137 // Optional MDF RCK-354
Length	2 in Shank Length
Overall Length	3 in
RPM	16,000
Shank	1/2 in
Angle	130 deg
Manufacturer	Amana Tool