Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010

Phone:817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171 Email: <u>info@eoasaw.com</u> Website: www.eoasaw.com



Item #RC-2239, Amana Tool Insert Carbide Mini Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 2+2 Flute Design 1-1/2 Dia x 1/2 x 6mm Shank Router Bit \$209.64

Thank you for shopping with us! CNC use only. Mini insert solid carbide spoilboard surfacing & rabbeting with scorer; great for cutting tight corners. Features unique 2+2 insert knife design that contains two cutting flutes and two up-shear scorers, which provide a smoother finish at the bottom of the cut than traditional two-knife style router bits. TIP!: To produce MDF simulated shaker cabinet doors use RC-2250 or RC-2252. Square corners with #45200 straight plunge router bit. Designed for planing & rabbeting the following materials:

- Balsa Core*
- Hardwood/Softwood*
- Chipboard*
- MDF
- · Fiberboard
- HDF/LDF
- Plastic*

*For optimal results and maximum insert life, replace inserts with optional general purpose knives (sold separately). Optional General Purpose Knives: #AMA-12 & RCK-70. Replacement screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005. Max cutting depth: 1/4. THIS TOOL IS NOT DESIGNED TO PLUNGE! You must ramp down to a depth of 1/4 in deep over a 20 in run. Use the max RPM allowed (24,000) and start the feed rate at about 320 in per minute, and go up until you get waves, then back down to a smooth cut/finish. WARNING: Proper torques rating to tighten down screws is 2-3Nm Torques. **Featuring:**

- 2+2 mini design for tighter corners
- · 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- Maximum cutting efficiency
- Faster material removal process
- · Longest tool life

Warning: Proper torques rating to tighten down screws is 2-3Nm Torques. **Torx key #5005 included** These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools.



SPECIFICATIONS	
Manufacturer	Amana Tool
Diameter	1 1/2 in
Cut Height, Length, or Width	1/2 in
Knives	HMA-12, HCK-70. Optional GP: AMA-12 & RCK-70. Optional Solid Wood DLC Coated: AMA-12-DLC & RCK-70-DLC.
Overall Length	1 13/16 in
RPM	24,000
Туре	With scorer & 2+2 insert knife design
Replacement Parts	Screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005.
Note	