

Edge of Arlington Saw & Tool, Inc.

124 South Collins

Arlington, TX 76010

Phone: 817-461-7171 • Fax: 817-795-6651

Toll Free: 888-461-7171

Email: info@eoasaw.com

Website: www.eoasaw.com



Item #RC-2250, Amana Tool Insert Carbide Mini Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 2+2 Flute Design 1-1/2" Dia x 1/2" x 1/2" Shank Router Bit (Industrial)

\$236.96

Thank you for shopping with us! Mini insert solid carbide spoilboard surfacing & rabbeting with scorer; great for cutting tight corners. Features unique 2+2 insert knife design that contains two cutting flutes and two up-shear scorers, which provide a smoother finish at the bottom of the cut than traditional two-knife style router bits. **TIP!:** To produce MDF simulated shaker cabinet doors use **RC-2250** or **RC-2252**. Square corners with **#45200** straight plunge router bit. Designed for planing & rabbeting the following materials:

- Balsa Core*
- Hardwood/Softwood*
- Chipboard*
- MDF
- Fiberboard
- HDF/LDF
- Plastic*

*For optimal results and maximum insert life, replace inserts with optional general purpose knives (sold separately). **Warning:** Proper torques rating to tighten down screws is 2-3Nm Torques. Optional General Purpose Knives: #AMA-12 & RCK-70. Replacement screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005. Max cutting depth: 1/4. THIS TOOL IS NOT DESIGNED TO PLUNGE! You must ramp down to a depth of 1/4 in deep over a 20 in run. Use the max RPM allowed (24,000) and start the feed rate at about 320 in per minute, and go up until you get waves, then back down to a smooth cut/finish. **Featuring:**


- 2+2 mini design for tighter corners
- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- Maximum cutting efficiency
- Faster material removal process
- Longest tool life

Torx key #5005 included These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools.

Create Your Own MDF SIMULATED SHAKER DOORS



To produce MDF Shaker cabinet doors use #RC-2250 or #RC-2252 and square corners with #45200 straight plunge router bit.



RCK-450 RCK-452
(MDF, Chipboard & Wood)



SPECIFICATIONS

Manufacturer	Amana Tool
Diameter	1 1/2 in
Cut Height, Length, or Width	1/2 in
Knives	HMA-12, HCK-70. Optional GP: AMA-12 & RCK-70. Optional Solid Wood DLC Coated: AMA-12-DLC & RCK-70-DLC.
Overall Length	2 5/16 in
RPM	24,000
Type	With scorer & 2+2 insert knife design
Replacement Parts	Screws: bottom-(2) #67155, key #5015; sides-(2) #67115, key #5005.
Note	--