

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)

---



### **Item #RC-2251, Amana Tool insert Carbide Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 2+2 Flute Design 2-1/2" Dia x 15/32 x 1/2" Shank Router Bit (Industrial)**

**\$314.42**

Edge of Arlington offers free shipping in the United States when you choose flat rate shipping.

Insert spoilboard, planing, and rabbeting router bit features unique 2+2 insert knife design. Contains two cutting flutes and two up-shear scorers, which provide a smoother finish at the bottom of the cut than traditional two-knife style router bits. Excellent results in MDF, balsa core, hardwood, softwood, and all man-made materials. A great tool for fast removal of materials over a large surface area. The scorer leaves an improved finish at the bottom of the cut. Utilizes 4-sided carbide inserts.

**TIP!:** To produce MDF simulated shaker cabinet doors use [RC-2250](#) or [RC-2252](#). Square corners with [#45200](#) straight plunge router bit.

#### **Designed for planing & rabbeting the following materials:**

- Balsa Core\*
- Hardwood/Softwood\*
- Chipboard/Plywood\*
- MDF
- Plastic\*
- Fiberboard
- HDF/LDF

\*For optimal results and maximum insert life, replace inserts with optional general purpose knives; sold separately.

**Warning:** Proper torques rating to tighten down screws is 2-3Nm Torques.

#### **Featuring:**

- 2+2 design
- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- Maximum cutting efficiency
- Faster material removal process
- Longest tool life

#### **Torx key #5005 included**

These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools.

Recommendations: For surfacing solid woods it is recommended to remove both bottom scorers.

For optimal results and maximum insert life, replace inserts with optional general purpose knives; sold separately.



## SPECIFICATIONS

**Cut Height, Length, or Width** 15/32 in

## SPECIFICATIONS

<b>Manufacturer</b>	Amana Tool
<b>Note</b>	Optional General Purpose knives: AMA-12 & RCK-70. Replacement screws: bottom, (2) #67155; sides, (2) #5005. Max cutting depth: 1/4. Warning: Proper torques rating to tighten down screws is 2-3Nm Torques.
<b>Overall Length</b>	2 1/2 in
<b>Shank</b>	
<b>Specs-Misc</b>	W/scorer & 2+2 insert knife design