

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)



### Item #RC-2256, Amana Tool Insert Carbide Mini Spoilboard Surfacing, Rabbeting, Flycutter, Slab Leveler & Surface Planer 1 1/2" Dia x 15/32" (12mm) x 6mm Shank Router Bit (Industrial)

**\$160.38**

Thank you for shopping with us!

CNC use only.

Designed for planing & rabbeting the following materials:

- MDF
- Fiberboard
- HDF/LDF
- Balsa Core\*
- Epoxy (Epoxy Resins)\*
- High Density Urethane (HDU Board)\*
- Plastic/Acrylic\*
- Plywood/Chipboard\*
- Hardwood/Softwood\*
- Ultra-High-Molecular-Weight Polyethylene (UHMWPE)\*

\*For optimal results and maximum insert life, replace inserts with optional general purpose knives #AMA-12 (sold separately).

#### Featuring:

- 4-sided solid carbide insert knives
- Exclusive carbide grade for highest quality of cut
- Maximum cutting efficiency
- Faster material removal process
- Longest tool life

These industrial router bits feature solid carbide insert knives with four cutting edges that allow users to flip the knife over when one side becomes dull, providing the highest-quality finish available on woodworking tools.

Warning: Proper torques rating to tighten down screws is 2-3Nm Torques.



## SPECIFICATIONS

**Manufacturer**

Amana Tool

## SPECIFICATIONS

<b>Cut Depth</b>	1/4 in Max Cut Depth
<b>Diameter</b>	1 1/2 in
<b>Cut Height, Length, or Width</b>	12 mm
<b>Knives</b>	HMA-12. Optional general purpose knives: AMA-12. Optional Solid Wood: AMA-12-DLC.
<b>Overall Length</b>	1 11/16 in
<b>RPM</b>	24,000
<b>Shank</b>	6 mm
<b>Replacement Parts</b>	Screw #67117
<b>Note</b>	Mini Design. . Warning: Proper Torques rating to tighten down screws is 2-3Nm Torques.