Edge of Arlington Saw & Tool, Inc.

124 South Collins Arlington, TX 76010 Phone:817-461-7171 • Fax: 817-795-6651 Toll Free: 888-461-7171 Email: info@eoasaw.com Website: www.eoasaw.com



TOOLS



Item #SD512, Freud SD500 Super Dado Sets CUTS \$351.50

Thank you for shopping with us! Application: Chip Free Dadoes in Veneered Plywoods & Laminates The SD500 Series cuts everything from veneered plywoods and laminates to solid wood. Chip- and splinter-free with a super smooth, flat bottom. The SD500 Series dado sets were the first to include a 3/32" thick chipper and has the flexibility of an adjustable dado to handle today's undersized plywood. This allows the cut width to be adjusted in 1/32" increments and doubles the number of slot widths available. A shim set is also included with the dado set for fine adjustments. Use on all table saws and radial arm saws for cutting slots, grooves, dadoes, and rabbets in softwood or hardwood. Set includes 2 blades, shim set, and 6 chippers. Freud Replacement Parts/Shim Sets

Chip Free Dadoes In

Veneered Plywoods And Lamninates **Recommended Use & Cut Quality** pplication HARDWOOD: SOFTWOOD: CHIP BOARD: PLYWOOD: LAMINATE: NON-FERROUS: CUT QUALITY:

The SD500 Series of dado sets cuts everything from ven The SD500 Series of dado sets cuts everything from veneered plywoods and laminates to solid wood, chip and splinter-free with a super smooth, flat bottom. The SD500 Series dado sets were the first to include a 3/32" thick chipper and has the flexibility of an adjustable dado to handle today's undersized pywood. This allows the cut width to be adjusted in 1/32" increments and doubles the number of slot widths available. A sims set is also included with the dado set for fine adjustments. Use on all table saws, and radial arm saws for cutting slots, grooves, dadoes, and rabbets in softwood or hardwood.

ſ	2 Blades		- Set Includes:		5:	Slot N Wicth	No. Chip 1/8	3/32	1/10
	5 a	TELLES"	P .)			11/32"	Ő	1	0
	5 -	AMPLOUD I	* 100			3/8" 13/32"	1	0	0
	12.00	No. of Concession, Name	-		ALC: NO TO THE REAL PROPERTY OF	7/16*	1	ó	- 61
	2.2. 3	Contraction of the local diversion of the loc	Shim Se	t T	6 Chippers	15/32"	1	ĭ	Ö
	122	-		Caution: Carbide	tips should never come into contact with	·/2*	2	Ó	0
		1. M. H.		each other. Alway	is use both outside blades and never use	17/32"	1	1	1
				chippers alone or	with just one outside blade.	9/16*	2	0	1
Ì				1000000000	Street and a second second second	19/32" 5/8"	2	1	0
	Item	Dia.	Teeth	Arbor	Chippers(C)	21/32"	2	1	4
	SD506	6'	20	5/8"	(4)1/8",(1)3/32",(1)1/16"	11/16"	3	ó	1
						23/32"	3	1	0
	SD508	8"	24	5/8"	(4)1/8",(1)3/32",(1)1/16"	3/4*	4	0	0
NIN	SD510	10"	32	1"	(4)1/8",(1)3/32",(1)1/16"	25/32"	3	1	1
	SD512	12"	36	1*	(4)1/8".(1)3/32".(1,1/16"	13/16" 29/32"	4	0	1
	Carbide Grade Chart • Increasing Hardness				The day	lipper lade	-	-120	
		205 H105 sing Impact	H815 H845 H		IB IB INT BLADE	HIGHT BLADE		R	15"
	_	_			ALL PROPERTY		_	_	-

SPECIFICATIONS				
Diameter	12 in			
Arbor	1 in			
Teeth	36			
Thickness	(4) 1/8 in, (1) 3/32 in, (1) 1/16 in Chippers			
Manufacturer	Freud Tools			