

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #TCHN65096, Everlast Truss & Component Saw - 650mm Dia 96-Tooth 30mm Bore 0.150" Plate 0.220" Kerf

\$825.96

Thank you for shopping with us!

These saws are the workhorses of truss plants and are designed to provide a long service life and excellent cutting performance. Countersunk (82°) holes will accept 5/16" flat head bolt.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance cross cutting.

SPECIFICATIONS	
Manufacturer	Everlast
Diameter	650 mm
Bore	30 mm
Countersink	
Grind	ATB
Hole Size	90mm; 100mm Bolt Hole Circle Dia
Hook Angle	10 deg
Kerf	0.220 in - 5.6 mm
Plate	0.150 in - 3.8 mm
Teeth	96
Machine	Hundegger