

Edge of Arlington Saw & Tool, Inc.

124 South Collins
Arlington, TX 76010
Phone: 817-461-7171 • Fax: 817-795-6651
Toll Free: 888-461-7171
Email: info@eoasaw.com
Website: www.eoasaw.com



Item #TCK1640K19, Everlast Truss & Component Saw - 16" Dia 40-Tooth 0.875" Bore 0.150" Plate 0.190" Kerf

\$320.88

Thank you for shopping with us!

These saws are the workhorses of truss plants and are designed to provide a long service life and excellent cutting performance. Countersunk (82°) holes will accept 5/16" flat head bolt.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance cross cutting.

SPECIFICATIONS	
Manufacturer	Everlast
Diameter	16 in
Bore	0.875 in
Countersink	--
Grind	ATB
Hole Size	2.25 in ; 2.265 in Bolt Hole Circle Dia
Hook Angle	10 deg
Kerf	0.190 in - 4.8 mm
Plate	0.150 in - 3.8 mm
Teeth	40
Machine	Koskovich