

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)

---



### **Item #TCK1640T25A, Everlast Truss & Component Saw - 16" Dia 40-Tooth 1.26" Bore 0.150" Plate 0.190" Kerf \$320.88**

Thank you for shopping with us!

These saws are the workhorses of truss plants and are designed to provide a long service life and excellent cutting performance. Countersunk (82°) holes will accept 5/16" flat head bolt.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance cross cutting.

| SPECIFICATIONS      |                                        |
|---------------------|----------------------------------------|
| <b>Manufacturer</b> | Everlast                               |
| <b>Diameter</b>     | 16 in                                  |
| <b>Bore</b>         | 1.26 in                                |
| <b>Countersink</b>  | --                                     |
| <b>Grind</b>        | ATB                                    |
| <b>Hole Size</b>    | 2.25 in; 2.265 in Bolt Hole Circle Dia |
| <b>Hook Angle</b>   | 10 deg                                 |
| <b>Kerf</b>         | 0.190 in - 4.8 mm                      |
| <b>Plate</b>        | 0.150 in - 3.8 mm                      |
| <b>Teeth</b>        | 40                                     |
| <b>Machine</b>      | Koskovich                              |