

## Edge of Arlington Saw & Tool, Inc.

124 South Collins  
Arlington, TX 76010  
Phone: 817-461-7171 • Fax: 817-795-6651  
Toll Free: 888-461-7171  
Email: [info@eoasaw.com](mailto:info@eoasaw.com)  
Website: [www.eoasaw.com](http://www.eoasaw.com)

---



**Item #TR1080A, Everlast 10" Dia 80-Tooth  
5/8" Bore .087" Plate 0.056" Thin Rim  
Plate 0.087" Kerf Thin Rim Saw - Alternate  
Top Bevel  
\$298.41**

Thank you for shopping with us!

The perfect saw to use where there is a need for a minimum of stock removal per cut, as in the cutting of plastic or veneer strips for edge banding. Maximum depth of cut on Thin Rim blade is 1-3/4 inches. Alternate design with thin saw plate and thick support hubs on both sides is available.

Alternate Top Bevel - ATB - Each tooth has top bevel typically between 10 and 20 degrees. Two teeth are required to provide a full kerf cut. Provides low cutting pressures, which reduce material tearing during the cutting process and provides a fine cutting finish. Best performance crosscutting.

SPECIFICATIONS	
<b>Manufacturer</b>	Everlast
<b>Bore</b>	5/8 in
<b>Diameter</b>	10 in
<b>Grind</b>	ATB
<b>Kerf</b>	0.087 in
<b>Plate</b>	Plate Thickness 0.087 in/2.2mmThin Rim Plate Thickness 0.056 in/1.4mm
<b>Teeth</b>	80
<b>Hook Angle</b>	5 deg